

# **SAFETY DATA SHEET**

#### 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

**Product name PLASTICOTE 70** 

Synonym(s) 2043 - MANUFACTURER'S CODE • CRC PLASTICOTE

1.2 Uses and uses advised against

Use(s) LACQUER • PROTECTIVE COATING

1.3 Details of the supplier of the product

Supplier name **CRC INDUSTRIES (AUST) PTY LIMITED** 

Address 9 Gladstone Road, Castle Hill, NSW, 2154, AUSTRALIA

Telephone (02) 9849 6700 Fax (02) 9680 4914 **Email** info@crcind.com.au Website www.crcindustries.com.au

1.4 Emergency telephone number(s)

**Emergency** 13 11 26 (PIC)

### 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO AUSTRALIAN WHS REGULATIONS

Aerosols - Flammable: Category 1 GHS classification(s)

Aerosols - Pressurised: Category 1

Serious Eye Damage / Eye Irritation: Category 2A

Specific Target Organ Systemic Toxicity (Single Exposure): Category 3

#### 2.2 Label elements

**DANGER** Signal word

Pictogram(s)





### Hazard statement(s)

H222 Extremely flammable aerosol.

Pressurized container: may burst if heated. H229

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

AUH066 Repeated exposure may cause skin dryness or cracking

### Prevention statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area. P271

P280 Wear protective gloves/protective clothing/eye protection/face protection.



SDS Date: 20 Jul 2016

Page 1 of 7 Version No: 3.1

#### PRODUCT NAME **PLASTICOTE 70**

#### Response statement(s)

P304 + P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsina

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P337 + P313 If eye irritation persists: Get medical advice/attention.

Storage statement(s)

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C.

Disposal statement(s)

P501 Dispose of contents/container in accordance with relevant regulations.

#### 2.3 Other hazards

No information provided.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
LIQUEFIED PETROLEUM GAS (CONTAINS < 0.1% 1,3 BUTADIENE)	68476-85-7	270-704-2	20 to 40%
ACETONE	67-64-1	200-662-2	23%
METHYL ETHYL KETONE (MEK)	78-93-3	201-159-0	14%
ADDITIVE(S)	-	-	<10%
XYLENE	1330-20-7	215-535-7	5 to 10%
ACRYLIC RESIN	-	-	10 to 30%
METHOXYPROPYL ACETATE	84540-57-8	283-152-2	<10%

# 4. FIRST AID MEASURES

### 4.1 Description of first aid measures

Eye If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to

stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.

Inhalation If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or

an Air-line respirator (in poorly ventilated areas). Apply artificial respiration if not breathing.

If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water.

Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.

Ingestion For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If

swallowed, do not induce vomiting. Ingestion is considered unlikely due to product form.

First aid facilities No information provided.

#### 4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

#### 4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

Skin

## 5. FIRE FIGHTING MEASURES

### 5.1 Extinguishing media

Dry agent, carbon dioxide or foam. Prevent contamination of drains and waterways.

### 5.2 Special hazards arising from the substance or mixture

Highly flammable aerosol. May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition. Aerosol may explode at temperatures exceeding 50°C. Eliminate all ignition sources including cigarettes, open flames, spark producing switches/tools, pilot lights, heaters, naked lights, mobile phones, etc when handling.

ChemAlert.

SDS Date: 20 Jul 2016 Version No: 3.1

Page 2 of 7

#### PRODUCT NAME PLASTICOTE 70

#### 5.3 Advice for firefighters

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

### 5.4 Hazchem code

2YE

- 2 Fine Water Spray.
- Y Risk of violent reaction or explosion. Wear full fire kit and breathing apparatus. Contain spill and run-off.
- E Evacuation of people in and around the immediate vicinity of the incident should be considered.

#### 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible.

#### 6.2 Environmental precautions

Prevent product from entering drains and waterways.

#### 6.3 Methods of cleaning up

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal.

#### 6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

#### 7. HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in a cool (< 50°C), dry, well ventilated area, removed from incompatible substances, heat or ignition sources and foodstuffs. Ensure aerosol containers/ cans are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for damaged/leaking containers. Large storage areas should have appropriate fire protection systems.

### 7.3 Specific end use(s)

No information provided.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1 Control parameters

### **Exposure standards**

Ingredient	Reference	TWA		STEL	
		ppm	mg/m³	ppm	mg/m³
Acetone	SWA (AUS)	500	1185	1000	2375
Liquefied petroleum gas (LPG)	SWA (AUS)	1000	1800	1000	1800
Methyl ethyl ketone (MEK)	SWA (AUS)	150	445	300	890
Xylene	SWA (AUS)	80		150	

### **Biological limits**

Ingredient	Determinant	Sampling Time	BEI
ACETONE	Acetone in urine		-
	Aniline released from hemoglobin in blood	End of shift	-
	p-Aminophenol in urine	End of shift	50 mg/L
METHYL ETHYL KETONE (MEK)	MEK in urine	End of shift	2 mg/L
XYLENE	Methylhippuric acids in urine	End of shift	1.5 g/g creatinine

Reference: ACGIH Biological Exposure Indices



#### PRODUCT NAME PLASTICOTE 70

#### 8.2 Exposure controls

Engineering controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof

extraction ventilation is recommended. Flammable/explosive vapours amy accumulate in poorly ventilated areas. Vapours are heavier than air and may travel some distance to an ignition source and flash back.

Maintain vapour levels below the recommended exposure standard.

PPE

**Eye / Face** Wear splash-proof goggles. **Hands** Wear nitrile or neoprene gloves.

**Body** When using large quantities or where heavy contamination is likely, wear coveralls.

**Respiratory** Where an inhalation risk exists, wear a Type A (Organic vapour) respirator.





### 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance CLEAR LIQUID (AEROSOL DISPENSED)

Odour SOLVENT ODOUR Flammability HIGHLY FLAMMABLE

Flash point 10°C (cc)
Boiling point 80°C

Melting point

Evaporation rate
pH

NOT AVAILABLE
3.0 (n-Butyl Acetate = 1)
NOT RELEVANT

Vapour density > 1 (Air = 1)

Specific gravity 0.90

Solubility (water) SLIGHTLY SOLUBLE Vapour pressure NOT AVAILABLE

Upper explosion limit 12 % Lower explosion limit 1.4 %

Partition coefficient
Autoignition temperature
Decomposition temperature
Viscosity
NOT AVAILABLE

9.2 Other information

% Volatiles 86 %

### 10. STABILITY AND REACTIVITY

### 10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

# 10.2 Chemical stability

Stable under recommended conditions of storage.

### 10.3 Possibility of hazardous reactions

Polymerization is not expected to occur.

## 10.4 Conditions to avoid

Avoid shock, friction, heavy impact, heat, sparks, open flames and other ignition sources.

## 10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), alkalis (e.g. sodium hydroxide), heat and ignition sources.

ChemAlert.

SDS Date: 20 Jul 2016 Version No: 3.1

Page 4 of 7

#### 10.6 Hazardous decomposition products

May evolve carbon oxides and hydrocarbons when heated to decomposition.

### 11. TOXICOLOGICAL INFORMATION

#### 11.1 Information on toxicological effects

Information available for the product: **Acute toxicity** 

Based on available data, the classification criteria are not met.

Information available for the ingredient(s):

Ingredient	Oral Toxicity (LD50)	Dermal Toxicity (LD50)	Inhalation Toxicity (LC50)
ACETONE	3000 mg/kg (mouse)	> 9400 uL/kg (guinea	44000 mg/m³/4 hours
METHYL ETHYL KETONE (MEK)	2737 mg/kg (rat)	6480 mg/kg (rabbit)	23500 mg/kg (rat)
XYLENE	4300 mg/kg (rat)	> 1700 mg/kg (rabbit)	4330-5984 ppm/6 hours

Skin Contact may result in drying and defatting of the skin, rash and dermatitis.

Eye Irritating to the eyes. Contact may result in irritation, lacrimation, pain and redness.

Sensitisation Not classified as causing skin or respiratory sensitisation. Mutagenicity Insufficient data available to classify as a mutagen. Insufficient data available to classify as a carcinogen. Carcinogenicity

Insufficient data available to classify as a reproductive toxin. Reproductive

STOT - single exposure

Over exposure may result in central nervous system (CNS) effects with headache, drowsiness and dizziness.

Repeated exposure to some solvents have been reported to cause adverse effects to the central nervous STOT - repeated exposure

system (CNS), liver and kidney. Over exposure to methyl ethyl ketone (MEK) in combination with certain

other solvents (eg n-hexane) may result in peripheral nerve damage.

Not classified as causing aspiration. **Aspiration** 

### 12. ECOLOGICAL INFORMATION

#### 12.1 Toxicity

No information provided.

#### 12.2 Persistence and degradability

No information provided.

### 12.3 Bioaccumulative potential

No information provided.

### 12.4 Mobility in soil

No information provided.

# 12.5 Other adverse effects

No information provided.

# 13. DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods

For small amounts, absorb contents with sand or similar and dispose of to an approved landfill site. Do not Waste disposal

puncture or incinerate aerosol cans. Contact the manufacturer/supplier for additional information (if required).

Legislation Dispose of in accordance with relevant local legislation.

#### 14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



SDS Date: 20 Jul 2016 Version No: 3.1



	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	1950	1950	1950
14.2 Proper Shipping Name	AEROSOLS	AEROSOLS	AEROSOLS
14.3 Transport Hazard Class	2.1	2.1	2.1
14.4 Packing Group	None Allocated	None Allocated	None Allocated

14.5 Environmental hazards No information provided

#### 14.6 Special precautions for user

 Hazchem code
 2YE

 GTEPG
 2D1

 EMS
 F-D, S-U

### 15. REGULATORY INFORMATION

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule Classified as a Schedule 5 (S5) Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Classifications Safework Australia criteria is based on the Globally Harmonised System (GHS) of Classification and

Labelling of Chemicals.

The classifications and phrases listed below are based on the Approved Criteria for Classifying Hazardous

Substances [NOHSC: 1008(2004)].

Hazard codes F+ Extremely flammable

Xi Irritant Xn Harmful

**Risk phrases** R12 Extremely Flammable.

R36 Irritating to eyes.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

Safety phrases S2 Keep out of reach of children.

S16 Keep away from sources of ignition - No smoking.

S25 Avoid contact with eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice

Inventory listing(s) AUSTRALIA: AICS (Australian Inventory of Chemical Substances)

All components are listed on AICS, or are exempt.

### 16. OTHER INFORMATION

**Additional information** 

The additive included in this product is described as a UV indicator.

AEROSOL CANS may explode at temperatures approaching 50°C.

#### PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

ChemAlert.

SDS Date: 20 Jul 2016 Version No: 3.1

#### HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Abbreviations ACGIH American Conference of Governmental Industrial Hygienists

CAS # Chemical Abstract Service number - used to uniquely identify chemical compounds

CNS Central Nervous System

EC No. EC No - European Community Number

EMS Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous

Goods)

GHS Globally Harmonized System

GTEPG Group Text Emergency Procedure Guide
IARC International Agency for Research on Cancer

LC50 Lethal Concentration, 50% / Median Lethal Concentration

LD50 Lethal Dose, 50% / Median Lethal Dose

mg/m³ Milligrams per Cubic Metre
OEL Occupational Exposure Limit

pH relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly

alkaline).

ppm Parts Per Million

STEL Short-Term Exposure Limit

STOT-RE Specific target organ toxicity (repeated exposure)
STOT-SE Specific target organ toxicity (single exposure)

SUSMP Standard for the Uniform Scheduling of Medicines and Poisons

SWA Safe Work Australia
TLV Threshold Limit Value
TWA Time Weighted Average

#### Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

### Prepared by

Risk Management Technologies 5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711 Fax: +61 8 9322 1794 Email: info@rmt.com.au Web: www.rmt.com.au.

[ End of SDS ]



SDS Date: 20 Jul 2016 Version No: 3.1